NewTec Design: Audio

CONO cubo



The elegant ceiling loudspeaker

Straight, purist design for ceiling mounting

The CONO cubo ceiling loudspeaker can be fixed directly to the ceiling and offers a minimalist look in high-quality anodised aluminium (CONO cubo S) and glass fibre-reinforced plastic. The reduced dimensions of 105 mm x 105 mm (CONO cubo S) and 110 mm x 110 mm make it a small powerhouse that complements the ceiling appearance with its object language, especially on ceilings with exposed concrete. The CONO cubo can also be installed on the wall. We recommend a mounting height of at least 2 meters. The ceiling loudspeaker is indispensable for correct playback in Dolby Atmos mode, especially to complement surround applications.

Technical Data

Application

Wall and ceiling speaker

Design

	CONO cubo 50	CONO cubo M	CONO cubo S	CONO cubo V
Colours	lacktriangle	lacktriangle	lacktriangle	lacktriangle
Dimensions	110 x 110 x 105 mm	110 x 110 x 105 mm	105 x 105 x 105 mm	110 x 110 x 105 mm
Material Housing	ABS plastic	ABS plastic	Aluminum	ABS plastic

Sound

	CONO cubo 50	CONO cubo M	CONO cubo S	CONO cubo V
Principle	Full-range 360°	Full-range 360°	Full-range 360°	Full-range 360°
Nominal power	50 W / 90 W	50 W / 90 W	100 W / 180 W	5 W
Impedance	16 Ω	4 Ω	8 Ω	100V / 1,9k Ω
Sensitivity	83.4 dB	85.5 dB	82.8 dB	86.8 dB
Maximum SRL	100 dB	102 dB	104 dB	99.5 dB
Frequency range	115-21,000 Hz	133-21,000 Hz	102-21,000 Hz	115-21,000 Hz

Installation

	CONO cubo 50	CONO cubo M	CONO cubo S	CONO cubo V
Weight	890 g	930 g	2.34 kg	1 kg
Connections	Block clamp	Print terminal	Golden-plated pole terminal	Block clamp