

CONO pendo



The flexible pendant speaker

The pendant speaker for high demands on good sound and stylish design

The pendant speaker CONO pendo can be directly fixed, for example, to the concrete ceiling and features a sight protection for the installation. The length of the CONO pendo's suspension can be adjusted variably according to the desired distance from the ceiling, thus optimizing the acoustic result. The height and position of the CONO pendo are adapted to the height and positions of the lights, visually creating a symbiosis between light and sound. In the standard version, the suspension length is 1.5 meters. Upon request, other lengths can also be provided.

Technical Data

Application

Pendulum speaker

Design

Colours



Dimensions

ø 134mm x 135 mm + cable length standard 1.5 m

Material

Glass fibre reinforced ABS plastic

Sound

	CONO pendo 50	CONO pendo M	CONO pendo S	CONO pendo V
Principle	Full-range 360°	Full-range 360°	Full-range 360°	Full-range 360°
Nominal power	50 W / 90 W	50 W / 90 W	100 W / 180 W	5-10-20 W einstellbar
Impedance	16 Ω	4 Ω	8 Ω	100V / 1,9k-940-470 Ω
Efficiency	83,4 dB	85,5 dB	82,8 dB	86,8 dB
Max. SPL	100 dB	102 dB	104 dB	99,5 dB
Frequency response	105-21.000 Hz	95-21.000 Hz	84-21.000 Hz	105-21.000 Hz

Installation

	CONO pendo 50	CONO pendo M	CONO pendo S	CONO pendo V
Weight	1,1 kg	1,2 kg	1,6 kg	1,4 kg
Power supply	Block terminal	Block terminal	Block terminal	Block terminal