SUB canto SMART



The smart subwoofer for the lighting track

Noble bass in the lighting track



Simple and straightforward design - can be perfectly integrated into the look of the lighting structure.
Its extraordinary efficiency ensures that large areas are supplied with pleasant low frequencies. Any number of subwoofers can be used. The volume of each individual subwoofer can also be adjusted by remote control during operation. Thanks to the wireless technology, no cabling is required and the subwoofer can be installed in no time at all ...even during ongoing business operations!

Product Codes

200612	SUB canto SMART - WHITE
200613	SUB canto SMART - BLACK

Technical Data

Application Active subwoofer for the lighting track

Design

Colours	● ○
Dimensions	150 x 150 x 475 mm
Material housing	Wood

Sound

Principle	Bass reflex with integrated amplifier and wireless module
Output power	50/100 W RMS
Equipment	Woofer driver
Efficiency	85,5 dB
Frequency response	40...185 Hz
Radio frequency	1,9 GHz n-DECT (frequency band: 1880-1900 MHz)
Transmitter	SMARTplayer

Installation

Weight	3.5 kg
Power supply	AC 100-240 V; 50/60 Hz; 0.5 A
Power consumption	Max. 60 W
Connections	Multi-adapter for lighting tracking tracks
Compatible with	Nordic Aluminium, Eutrac®, Global, Nuco, Staff, Ivela, Zumtobel etc.