CONO puro SMART







The smart built-in loudspeaker

Pure optics for pure sound

The new CONO puro built-in loudspeaker fits perfectly with the “small and simple” design trend. The diameter is just 150mm. The music is received reliably via 1.9 GHz radio technology. Furthermore, the new quick-release fastener eliminates the need for screws. This allows for quick installation and the screwless design also ensures simple elegance. The material thickness of the ring is kept to a minimum so that the speaker can lie flat on the ceiling. The ceiling cut-out required for installation is 120 mm and the installation depth is 140 mm.

Product Codes

200521	CONO puro SMART - SILVER
200522	CONO puro SMART - WHITE
200523	CONO puro SMART - BLACK

Technical Data

Application

In-ceiling loudspeaker

Design

Colours	● ○ ●
Dimensions	Ø 150 mm / h: 160 mm
Material housing	Ring made from glass fibre reinforced ABS plastic

Sound

Principle	360° - Speaker with integrated amplifier and wireless module
Output power	40 W RMS
Equipment	NewTec KA10 loudspeaker 50W 4Ω
Efficiency	85,5 dB
Max. SPL	102 dB
Frequency response	105-20.000 Hz
Radio frequency	1,9 GHz n-DECT (frequency band: 1880-1900 MHz)
Transmitter	SMARTplayer

Installation

Ceiling cut-out	120 mm
Ceiling thickness	min. 6 mm / max. 25 mm
Installation depth without backbox	90 mm
Installation depth with backbox	140 mm
Weight	648 g
Power supply	AC 100-240 V; 50/60 Hz; 0.5 A
Connections	Connection terminal